

USER INFORMATION NOTICE

**UK MANUFACTURER
WORK IN PROGRESS
(WIP)LTD.
3A HOLY WELL HILL
ST ALBANS AL1 1ER, UK**

**EU REPRESENTATIVE
WIP (WORKWEAR EUROPE) LTD
FIRST FLOOR BLOCK ONE
QUAYSIDE BUSINESS PARK
DUNDALK CO LOUTH IRELAND A91 DP8R**

- This safety footwear complies with the EU/UKCA Directive for Personal Protective Equipment (Regulation 2016/425) and meets the requirements of the European standard EN ISO 20345:2011. It is certified by SGS FIMKO OY, Takomotie 8, FI-00380 Helsinki, Finland, (Notified Body 0598)/SGS United Kingdom Limited, Rossmore Business Park, Ellesmere Port, Cheshire CH65 3EN. (Notified Body 0120).
- Safety Footwear is manufactured using both synthetic and natural materials which conform to the relevant sections of EN ISO 20345:2011 for performance and quality.
- Safety Footwear is designed to minimise the risk of injury that could be inflicted by the wearer during use. It is designed to be used in conjunction with a safe working environment and will not completely prevent injury if an accident occurs which exceeds the testing limits of EN ISO 20345:2011
- The footwear protects the wearer's toes against risk of injury from falling objects and crushing when worn in industrial and commercial environments where potential hazards occur with the following protection plus, where applicable, additional protection.

Impact protection provided is 200 Joules.

Compression protection provided is 15,000 Newton's.

Additional protection may be provided, and is identified on the product by it marking as follows

Marking code	
Penetration resistance (1100 Newton's)	P
Electrical properties:	
Conductive (Max 100 kΩ)	C
Antistatic (Range of 100 kΩ to 1000 MΩ)	A
Electrically insulating footwear	I
Resistance to inimical environments:	
Insulation against heat	HI
Insulation against cold	CI
Energy absorption of seat region (20 Joules)	E
Water resistance	WR
Metatarsal protection	M
Ankle protection	AN
Cut resistant upper	CR
Upper	
Water penetration and water absorption	WRU
Outsole	
Resistance to hot contact	HRO
Resistance to fuel oil	FO

Penetration resistance

In this footwear, **Metal penetration-resistance insert** is used.

The penetration resistance of this footwear has been measured in the laboratory using a truncated nail of diameter 4,5 mm and a force of 1100 N.

Higher forces or nails of smaller diameter will increase the risk of penetration occurring. In such circumstances alternative preventative measures should be considered.

Two generic types of penetration resistant insert are currently available in PPE footwear.

These are metal types and those from non-metal materials. Both types meet the minimum requirements for penetration resistance of the standard marked on this footwear but each has different additional advantages or disadvantages including the following:

Metal: Is less affected by the shape of the sharp object / hazard (ie diameter, geometry, sharpness) but due to shoemaking limitations does not cover the entire lower area of the shoe;

Non-metal – May be lighter, more flexible and provide greater coverage area when compared with metal but the penetration resistance may vary more depending on the shape of the sharp object / hazard (ie diameter, geometry, sharpness)

For more information about the type of penetration resistant insert provided in your footwear please contact the manufacturer or supplier detailed on these instructions.

- It is important that the footwear selected for wear must be suitable for the protection required and wear environment.
Where a wear environment is not known, it is very important that consultation is carried out between the seller and the purchaser to ensure, where possible, the correct footwear is provided.
- To ensure the best service and wear from footwear, it is important that the footwear is regularly cleaned and treated with a good proprietary cleaning product. Do not use any caustic cleaning agents. Where footwear is subjected to wet conditions, it shall, after use, be allowed to dry naturally in a cool, dry area and not be force dried as this can cause deterioration of the upper material. When stored on normal conditions (temperature, and relative humidity), the obsolescence date of a footwear is generally:
 - 10 years after the date of manufacturing for shoes with upper leather and rubber sole
 - 3 years after the date of manufacturing for shoes including PU"
- This footwear has been successfully tested against EN ISO 20345:2011 clause 5.3.5 for slip resistance and the following marking symbols apply.

Marking of product for slip resistance properties	Marking code
Ceramic tile with sodium lauryl sulphate	SRA
Steel with glycerol	SRB
Ceramic tile with sodium lauryl sulphate & Steel with glycerol	SRC

*Note: Slippage may still occur in certain environments.

- Electrically-resistant footwear is supplied with an Information Notice as required by EN ISO 20345:2011 outlining the purpose, use of footwear, requirement for regular testing when in use, to ensure footwear stays within specific resistance levels. Footwear shall be kept clean and free from contamination between the sole surface and flooring to retain satisfactory contact. The flooring shall be of an electrically-resistant level to ensure the footwear can dissipate static electricity to earth.
- If the footwear is cared for and worn in the correct working environment and stored in dry ventilated conditions, it should give a good wear life, without premature failure of the outsole, upper and upper stitching. The actual wear life for footwear is dependent on the type of footwear, environmental conditions which can affect the wear, contamination and degradation of the product.
- Marking on footwear denotes that the footwear is licensed according to the PPE Directive and is as follows:

Examples of markings	Explanation
STANLEY FATMAX	Identification Mark
CE/UKCA	CE mark
EN ISO 20345:2011	Number of European standard
9 (43)	Footwear size
01/2022	Quarter and year of manufacture
S3	Category of protection
A	Additional property code, e.g. Antistatic
GR1	Group Identification

Categories of safety footwear:

Category	Type (*) and (**II)		Additional Requirement
SB	I	II	Safety basic requirements
S1	I		Closed seat region Antistatic properties Energy absorption at the seat region Resistance to fuel oil
S2	I		As S1 plus Water penetration and absorption of the upper
S3	I		As S2 plus Penetration resistance Cleated outsole
S4		II	Closed seat region Antistatic properties Energy absorption at the seat region Resistance to fuel oil
S5		II	As S4 plus Penetration resistance Cleated outsole
*Type I footwear is made from leather and other materials excluding all-rubber or all-polymeric footwear			
** Type II All –rubber (i.e. entirely vulcanized) or all-polymeric (i.e. entirely moulded) footwear			
SBH	Hybrid footwear		

- If the footwear becomes damaged, it will not continue to give the specified level of protection and to ensure that the wearer continues to receive the maximum protection, the footwear should immediately be replaced.
- The packaging provided with the footwear at the point of sale is to ensure that the footwear is delivered to the customer in the same condition as when dispatched; the carton can also be used for storing the footwear when not in wear. When the boxed footwear is in storage, it should not have heavy objects placed on top of it, as this could cause breakdown of its packaging and possible damage to the footwear.
- The footwear is supplied with a removable insock. Please note the testing was carried out with the insock in place. The footwear shall only be used with the insock in place. The insock shall only be replaced by a comparable insock.

Antistatic footwear

Antistatic footwear should be used if it is necessary to minimize electrostatic build-up by dissipating electrostatic charges, thus avoiding the risk of spark ignition of, for example flammable substances and vapours, and if risk of electric shock from any electrical apparatus or live parts has not been completely eliminated. It should be noted, however, that antistatic footwear cannot guarantee an adequate protection against electric shock as it introduces only a resistance between foot and floor. If the risk of electric shock has not been completely eliminated, additional measures to avoid this risk are essential. Such measures, as well as the additional tests mentioned below should be a routine part of the accident prevention programme of the workplace.

Experience has shown that, for antistatic purpose, the discharge path through a product should normally have an electrical resistance of less than 1000 M at any time throughout its useful life. A value of 100 k is specified as the lowest limit of resistance of a product when new, in order to ensure some limited protection against dangerous electric shock or ignition in the event of any electrical apparatus becoming defective when operating at voltages up to 250 V. However, under certain conditions, users should be aware that the footwear might give inadequate protection and additional provisions to protect the wearer should be taken at all times.

The electrical resistance of this type of footwear can be changed significantly by flexing, contamination or moisture. This footwear will not perform its intended function if worn in wet conditions. It is, therefore, necessary to ensure that the product is capable of fulfilling its designed function of dissipating electrostatic charges and also of giving some protection during its whole life. The user is recommended to establish an in-house test for electrical resistance and use it at regular and frequent intervals.

Classification I footwear can absorb moisture if worn for prolonged periods and in moist and wet conditions can become conductive.

If the footwear is worn in conditions where the soiling material becomes contaminated, wearers should always check the electrical properties of the footwear before entering a hazard area.

Where antistatic footwear is in use, the resistance of the flooring should be such that it does not invalidate the protection provided by the footwear.

In use, no insulating elements, with the exception of normal hose, should be introduced between the inner sole of the footwear and the foot of the wearer. If any insert is put between the inner sole and the foot, the combination footwear/insert should be checked for its electrical properties.



(UK) DECLARATION OF CONFORMITY

PPE (*BERGEN* footwear):

Name and address of the manufacturer and, where applicable, his authorised representative:

UK Manufacturer
Work in Progress(WIP)Ltd.
3A Holy well Hill St Albans AL1 1ER, UK

This declaration of conformity is issued under the sole responsibility of the manufacturer:

Object of the declaration
(*Footwear BERGEN*):

The object of the declaration described in point 4 is in conformity with the relevant Union harmonisation legislation:

Personal Protective Equipment Regulation (2016/425) as brought into UK law and amended

References to the relevant harmonised and designated standards used, including the date of the standard, or references to the other technical specifications, including the date of the specification, in relation to which conformity is declared: (*EN ISO 20345: 2011*)

Where applicable, the notified body ... (*SGS United Kingdom Limited,0120*)... performed type-examination (Module B) and issued the type-examination certificate ... (*no.: 0120/PPE/220007*).

Where applicable, the PPE is subject to the conformity assessment procedure under surveillance of the notified body ...

Additional information:

Signed for and on behalf of:

Work in Progress(WIP)Ltd.
3A Holy well Hill St Albans AL1 1ER, UK

W.I.P.
WORK IN PROGRESS

For and on behalf of:

WIP(Work in Progress) Ltd

Steve Bowen
Group Quality Director

Date of issue: [27/08/2022]



**EU DECLARATION OF CONFORMITY
Personal Protective Equipment Regulation (EU) 2016/425**

PPE (BERGEN footwear):

Name and address of the manufacturer and, where applicable, his authorised representative:

UK Manufacturer
Work in Progress(WIP)Ltd.
3A Holy well Hill St Albans AL1 1ER, UK

This declaration of conformity is issued under the sole responsibility of the manufacturer:

**Object of the declaration
(Footwear BERGEN):**

**The object of the declaration described in point 4 is in conformity with the relevant Union harmonisation legislation:
Personal Protective Equipment Regulation (EU) 2016/425**

References to the relevant harmonised standards used, including the date of the standard, or references to the other technical specifications, including the date of the specification, in relation to which conformity is declared: (EN ISO 20345: 2011)

Where applicable, the notified body ... (SGS Fimko Lta,0598) ... performed the EU type-examination (Module B) and issued the EU type-examination certificate ... (no.: 0598/PPE/22/2016).

Where applicable, the PPE is subject to the conformity assessment procedure ... under surveillance of the notified body ...

Additional information:

Signed for and on behalf of:

Work in Progress(WIP)Ltd.
3A Holy well Hill St Albans AL1 1ER, UK

W.I.P.
WORK IN PROGRESS

For and on behalf of:

WIP(Work in Progress) Ltd

Steve Bowen
Group Quality Director.

Date of issue: [27/08/2022]